

MONITOR • MANAGE • CONTROL • SECURE • MONITOR • MANAGE

ContentKeeper SB

Supports from 5 to 100 users, with Ethernet Interfaces of 10/100Mbit/s.

ContentKeeper SME

Supports sites up to approximately 2,500 users with Ethernet Interfaces of 10/100Mbit/s.

ContentKeeper SME 2

Suitable for up to 5,000 users with Gigabit Ethernet Interfaces.

ContentKeeper LE2

Suitable for larger Enterprises, supporting approximately 2,000 to 50,000 users and Gigabit Ethernet Interfaces.

ContentKeeper VLE

Designed for Enterprises with more than 10,000 users and extends to Enterprises with 100,000 plus users with Optical and Copper Gigabit Ethernet Interfaces.



ContentKeeper Technologies

specialises in producing state-of-the-art appliances and software designed to assist Corporate, Government, educational and ISP clients to better manage their organisation's access to internet resources.

Specifications

Transparent Ethernet Bridge 2 x 10/100Mbit/s UTP bridging ports (CK SB & SME) OR 2 x 10/100/1000Mbit/s UTP bridging ports (CK LE2) OR 2 x optical Gigabit / UTP (VLE)
Plus
1 x 10/100Mbit/s UTP management port
1 x High Availability Module (HAM) interface port
1 x Console port (serial RS232C)

Fail safe AND fail over design **Browser based Management**

- High Availability Module (HAM)
 - Automatic fail-safe electro-mechanical Ethernet bypass (both UTP and optical options)
 - Secure local and remote web browser based management
- Security**
- Hack proof transparent Ethernet bridge
 - Helps protect against web based Virus attacks, Spyware, Malware, known Trojans, Worms etc

Rack mountable models –

- CK SME: 1 rack unit
- CK SME2: 1 rack unit
- CK LE2: 1 rack unit
- CK VLE: 2 rack units
- CK SB: Desktop unit

Plug and Play Installation

- Network transparent bridge device

ContentKeeper Technologies
Asia Pacific (Headquarters)
218 Northbourne Avenue
Braddon, ACT 2612 Australia
Tel +61 (2) 6261 4950
Fax +61 (2) 6257 9801

Europe (UK)
ContentKeeperTechnologies Europe
Box 7868, Crowthorne, Berkshire
RG45 6XY, United Kingdom
Tel +44-(0)-1344-752 740
Fax +44-(0)-1344-780 332

